

Synthesis and structural features of Fe_3O_4 , $\gamma\text{-Fe}_2\text{O}_3$ and $\text{Co}_x\text{Fe}_{2-x}\text{O}_4$ materials for local low-frequency magnetic hyperthermia of cancer tumors

D. Kotsikau^a, V. Pankov^a, B. Kashevsky^b, S. Kashevsky^b, I. Prokhorov^b, E. Petrova^a

^a*Belarusian State University, Minsk, Belarus, e-mail: kotsikau@bsu.by*

^b*Heat and Mass Transfer Institute, Minsk, Belarus*

Ferrimagnetic iron oxides (Fe_3O_4 , $\gamma\text{-Fe}_2\text{O}_3$) are promising materials for medical applications due to their suitable magnetic properties and high biocompatibility. Doping of $\gamma\text{-Fe}_2\text{O}_3$ with cobalt is known to improve its functional characteristics for low-frequency magnetic hyperthermia. The samples of Fe_3O_4 , $\gamma\text{-Fe}_2\text{O}_3$ and ferrite-type $\text{Co}_x\text{Fe}_{2-x}\text{O}_4$ were prepared in a form of sol and powder by chemical deposition from water solutions. The influence of synthesis conditions on the structural and magnetic features of the obtained materials was studied. The best material for hyperthermia appeared to be Co-doped $\gamma\text{-Fe}_2\text{O}_3$ (2.6 mol % of Co) heated at 300 °C. It has a structure of $\gamma\text{-Co}_x\text{Fe}_{2-x}\text{O}_4$ solid solution and a grain size of ~50 nm. The sample is characterized by energy dissipation $W \sim 4$ J/kg in physiological magnetic field ($H = 800$ Oe, $f = 430$ Hz).